



A Product of the
Cooperative Engineering Program

SAE J1555 NOV85

**Design Guidelines for
Optimizing
Automobile Collision
Damage Resistance,
Repairability and
Serviceability**

SAE Recommended Practice
Issued November 1985

SAENORM.COM : Click to view the full PDF of j1555-198511

**S.A.E.
LIBRARY**

SAENORM.COM : Click to view the full PDF of j1555 - 198511

**No part of this publication may be reproduced in any form,
in an electronic retrieval system or otherwise, without the
prior written permission of the publisher.**

Copyright 1986 Society of Automotive Engineers, Inc.

RATIONALE:

Not applicable.

RELATIONSHIP OF SAE STANDARD TO ISO STANDARD:

Not applicable.

REFERENCE SECTION:

Tech-Cor Collision Data Report, June 1982.

APPLICATION:

The intent of this Recommended Practice is to present a list of basic guidelines for optimizing motor vehicle resistance to collision damage, facilitate repairability and serviceability. The guidelines are intended to assist automobile engineers, designers and management personnel as they contemplate designs for advanced models. Then, damageability, repairability, etc., can be integrally considered with such other design parameters as cost, weight, manufacturability, warranty, styling, performance, etc.

COMMITTEE COMPOSITION:

DEVELOPED BY THE SAE MAINTENANCE DIVISION:

N. H. Pulling, Luberty Mutual Research Center, Hopkinton, MA - Chairman
R. A. Bollman, Chrysler Corporation, Detroit, MI
D. B. Cameron, Tech-Cor, Inc., Wheeling, IL
R. Cossette, Lehman's Garage, Minneapolis, MN
K. H. Digges, Nat'l. Hwy. Traffic Safety Admin., Washington, DC
J. D. Fobian, American Automobile Association, Falls Church, VA
M. R. Francis, AAMCO Transmissions, Inc., Bala Cynwyd, PA
W. E. Guthier, Alliance of American Insurers, Schaumburg, IL
G. V. Haddon, Broad Run Enterprises, Honey Brook, PA
S. Jenio, TRW, Inc., Sterling Hts., MI
G. R. Mecherle, State Farm Mutual Auto Insurance Co., Bloomington, IL
G. W. Merwin III, Automotive Service Councils, Inc., Elmhurst, IL
P. M. Miller, MGA Research Corp., Akron, NY
J. C. Murphy, ADP Corporation, Rolling Meadows, IL
B. C. Parr, State Farm Insurance Co., Bloomington, IL
R. B. Pinkerton, TRW Inc., Cleveland, OH
B. Schimpke, Ford Motor Company, Dearborn, MI
W. Shapiro, Volvo of Amer. Corp., Rockleigh, NJ
J. N. Silver, Inter. Ind. Conf. Auto Collision Rep., Des Plaines, IL
R. H. Weiner, Nat'l. Inst. for Auto Serv. Excel., Reston, VA



400 COMMONWEALTH DRIVE. WARRENDALE PA 15096

MAINTENANCE PRACTICE

SAE J1555

Issued Nov. 1985

DESIGN GUIDELINES FOR OPTIMIZING AUTOMOBILE COLLISION DAMAGE RESISTANCE, REPAIRABILITY AND SERVICEABILITY

1. **PURPOSE:** The intent of this SAE Recommended Practice is to present a list of basic guidelines for optimizing motor vehicle resistance to collision damage, facilitate repairability and serviceability. The guidelines are intended to assist automobile engineers, designers and management personnel as they contemplate designs for advanced models. Then, damageability, repairability, etc., can be integrally considered with such other design parameters as cost, weight, manufacturability, warranty, styling, performance, etc.

The guidelines have been compiled from several sources by the Collision Repair Division of the SAE Highway Vehicle Maintenance and Repair Council in cooperation with Tech-Cor Research. Basically, these guidelines reflect field experience with damaged vehicles.

Separate lists have been developed for damageability, repairability, and serviceability to assist the designer and the engineer in establishing appropriate priorities. Thus, it is recognized that there may be instances where an improvement in damageability may reduce repairability. It is felt, however, that the lists will generally permit independent consideration.

Within the context of recognized design tradeoffs, it is suggested that a basic objective should be that the cost of repairing a vehicle should be at the lowest level in areas where collision involvement frequency is the highest, i.e., around the exterior perimeter of the vehicle.

SAE Technical Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be reaffirmed, revised, or cancelled. SAE invites your written comments and suggestions.

Comments on this Recommended Practice are invited from interested parties and can be submitted in writing to SAE Headquarters.

2. DAMAGEABILITY ISSUES:

2.1 Component Vulnerability:

- Collision involvement frequency of front end, left and right corners is 60%; the rear end is 30% and 5% each for the sides. (See Ref. 1.)
- Can an expensive component be moved to a less vulnerable location?
- If a component cannot be moved, can it be made more easily repairable or cheaper to replace?

2.2 Resistance to Damage:

- When involved in a low speed impact, does the component resist minor damage without being completely destroyed?

2.3 Transfer of Damage:

- Can a design be modified to allow a component to absorb low speed impact energy?
- Are components collapsing too readily and allowing the load path to reach more expensive components?

2.4 Damageability Improvement - Examples:

- Bumper systems meet a 5 mph no damage standard, including corners.
- Prevention of front fender intrusion into windshield.
- Hood is designed to limit transmittal of damage to the windshield.
- Upper rail reinforcement should provide protection to mechanical components by extending from the cowl/firewall forward to the radiator core support.
- Plastic grille is separate from headlamp bezel and is designed to limit damage to headlamp and radiator.
- Adequate clearance is provided between hood lock support and radiator.
- Radiator has floating mounts to absorb minor impact damage.
- Cooling fans designed to reduce damage to the radiator core under minor impact.
- Air conditioning receiver/dryer is located in a minimum vulnerability area.
- Expensive electronic components are located in a protected area or else in a minimum vulnerability area.

2.4 (Continued):

- Rack and pinion is mounted in a protected location.
- Adequate clearance is provided for front drive shafts and other underhood mechanical components.
- Fuel tank is protected against puncture by framerails, suspension components, etc.

3. REPAIRABILITY ISSUES:

3.1 Ease of Repair:

- Are welded components or assemblies readily accessible for straightening or removal?
- Can components or assemblies be repaired without removal from the vehicle?
- Is the component material economically repairable?
- Can service parts be located using alignment holes, dimples, or cutouts on mating flanges for ease of reassembly?
- Is there information provided which describes special welding, assembly sequence or corrosion protection procedures?

3.2 Damage During Repair:

- Can components be repaired without causing further damage to adjacent components?

3.3 Cost of Repair:

- Is the repair cost associated with a design inordinately more expensive than similar competitive designs?
 1. Does it take more time?
 2. Do the parts cost more?

3.4 Repairability Improvement - Examples:

- An approved sectioning procedure exists for the following components:
 - * Front and rear rails, forward or rearward of suspension mounting
 - * Rear floor pan at or rearward of suspension mounting
 - * Rocker panel (full and partial)
 - * Windshield and lock pillars

3.4 (Continued):

- Hood, decklid, fenders, and doors are bolted on for ease in replacement and have adequate adjustability (+6 mm) minimum.
- Upper engine compartment, rear body, and underbody component alignment reference marks are provided.
- Mating component flanges have matching cutouts for alignment.
- Openings in inner body structure are provided to allow access for straightening door outer and quarter panels.
- Panel joints are designed so that the higher frequency replacement panels are easily accessible.
 - * Front apron extension overlaps strut tower and upper rail reinforcement.
 - * Front and rear rail extensions overlap respective inboard portions.
 - * Front side member overlaps front floor reinforcement.
 - * Lower back panel overlaps the outer quarter panel and the rear floor pan.
- Rocker panel has increased resistance to deformation during straightening of front or rear rails.
- All major plastic components have molded in material identification codes for bonding and welding.

4. SERVICEABILITY ISSUES:4.1 Component Accessibility:

- If a major component has to be removed, do other parts have to be removed before the component is accessible?

4.2 Part Availability:

- Are assemblies or large parts located in vulnerable areas serviced in sub-assemblies or partial panels?

4.3 Part Cost:

- Are serviced parts, partial panels, and sub-assemblies competitively priced?